SPH426
MEDIUM–DUTY FUME EXTRACTOR

Our most popular model for light and medium duty applications, the SPH426 fume extractor uses a multi-stage filtration system containing pre-filter, HEPA and chemical filters (up to 50 lbs / 23 kg of chemical filtration media) and the LaserBlue gel seal which guarantees ZERO FILTER BYPASS.

Knock-out Pad AG168

2˝ Pleated Filter F071

4˝ High Capacity Filter F164

2˝ HEPA Filter F074

6˝ HEPA Filter F075

8˝ Carbon Filter AG097

12˝ Carbon Filter AG098

CAPTURE ARMS AVAILABLE

3087792
CONFORMS TO:
UL STD 507
CERTIFIED TO:
CSA STD C22.2 NO 113
Intertek

✓ RoHS COMPLIANT

CE

APPLICATION	FILTER SEQUENCE	EFFICIENCY	CFM	POWER REQUIREMENTS	DIMENSIONS (HXWXD)	SHIPPING WEIGHT	PART #
GAS/ODOR AND PARTICLES/DUST	Knock-out Pad AG168 2˝ Pleated Filter F071 2˝ HEPA Filter F074 8˝ Carbon Filter AG097	MERV 6 MERV 10 MERV 17 N/A	282 Nominal (90˝ W.C.)	120V/1PH/60Hz 12A 230V/1PH/50Hz 8A	24x12x15 in 76x30x38 cm	100 lbs 45 kg	SPH426-T4G-EA8 SPH425-T4G-EA8
GAS/ODOR ONLY	Knock-out Pad AG168 12˝ Carbon Filter AG098	MERV 6 N/A	282 Nominal (90˝ W.C.)	120V/1PH/60Hz 12A 230V/1PH/50Hz 8A	24x12x15 in 76x30x38 cm	115 lbs 52 kg	SPH426-T4G-EB8 SPH425-T4G-EB8
PARTICLES/DUST ONLY	Knock-out Pad AG168 2˝ Pleated Filter F071 4˝ High Capacity Filter F164 6˝ HEPA Filter F075	MERV 6 MERV 10 MERV 11 MERV 17	282 Nominal (90˝ W.C.)	120V/1PH/60Hz 12A 230V/1PH/50Hz 8A	24x12x15 in 76x30x38 cm	90 lbs 41 kg	SPH426-T4G-EH38 SPH425-T4G-EH38

FILTERS

	PART #
Knock-out Pad (box of 12)	AG168
2˝ Pleated Filter (box of 6)	F071
4˝ High Capacity Filter	F164
6˝ HEPA Filter, 99,97% efficiency at 0.3μm	F075
2˝ HEPA Filter, 99,97% efficiency at 0.3μm	F074
12˝ Chemical Module with Media	AG098
8˝ Chemical Module with Media	AG097
Replacement chemical media for AG098 module	AG110
Replacement chemical media for AG097 module	AG119

⚠ NOTE: Quatro products are NOT INTENDED for use with explosive or flammable substances or environments.
Refer to your MSDS sheets for details and guidance.

· **i**Series features: digital variable speed control, visual and audible alarms, circuit breaker and 9 pin D-Sub interface
· **a**Series features: analog speed control and circuit breaker

OPTIONS & ACCESSORIES

	PART #
4˝(standard), single or dual 3˝, 2˝, 1.5˝ Inlets	Contact Us
4˝ Exhaust discharge kit	Contact Us
Custom chemical filter	Contact Us
Source capture arms	Contact Us
Brushless motor	Contact Us

Quatro reserves the right to modify any specifications, at any time without prior notice.

QUATRO
AIR TECHNOLOGIES INC.